

## Partaker 6 LAN Firewall S03



### Product Features

Sheet metal structure, fuel injection process, fan design;

Onboard Intel Celeron/Pentium/Core Series Processor;

Support 1 x DDR3L memory; 2 x DDR4 Memory

Support 1 x mSATA SSD; 1 x 2.5 inch SSD/HDD

Support OS:



### Product Specifications

|                 |  |
|-----------------|--|
| Model           | Partaker S03   |
| Case Color      | Silver/Gray/Red/Black/White  |
| Case Material   | Iron Metal   |
| Processor       | Intel Atom D525, dual-core four-thread, main frequency: 1.8GHz<br>Intel Core i3-3110M, (1005M/I3-2350M/I5-2520M/3320M/I7-3520M/3610M/3630QM)<br>Intel Celeron J4125, quad-core and four-thread, main frequency: 2.0GHz(optional N4000)<br>Intel Celeron N5105, quad-core and four-thread, main frequency: 2.0GHz(optional N5100)<br>Intel Pentium 4405U (optional 3865U/I3-7100U/8130U/I5-7200U/8250U/I7-7500U/8550U)<br>Intel Core I3-1115G4 (optional I5-1135G7/I7-1165G7) |
| BIOS            | AMI EFI BIOS   |
| Ram             | 1 x DDR3 1066/1333 SODIMM Ram Slot, Up to 4GB<br>1 x DDR3L 1600MHz SODIMM Ram Slot, Up to 8GB<br>2 x DDR4 2400 MHz SODIMM memory slots, up to 8GB<br>2 x DDR4 2933 MHz SODIMM memory slots, up to 32GB<br>2 x DDR4 2133 MHz SODIMM memory slots, up to 64GB<br>2 x DDR4 3200 MHz SODIMM memory slots, up to 64GB   |
| Storage         | 1 x mSATA SSD, 1 x 2.5 inch SATA   |
| Graphic         | Intel HD Graphics/Intel Iris Xe Graphics   |
| Display port    | 1 x VGA  |
| I/O             | DC-IN, 2 x USB3.0, 6 x LAN, 1 x VGA, 1 x PWR/HD, 1 x Console, Wifi Holes   |
| Expand          | Support 1 MINI PCIE channel (can be WIFI/Bluetooth/4G)   |
| Ethernet        | Intel I225/I226/82574L/82583V/I211 adaptive network card interface(Depend on CPU)  |
| Other functions | Power-on boot, scheduled boot, wake-up on LAN, PXE boot, watchdog  |
| Power           | Industrial grade power supply Taiwan MEAN WELL LRS-50-12 Input: 100-240V~1.0A  |

|                |  |
|----------------|--|
|                | Output: 12V4.2A  |
| Certification  | CE FCC CCC ROHS  |
| Size           | 440 x 250 x 45(mm)(excluding mounting ears)                                  |
| Operating Temp | -0~+50° C (commercial HDD), -20° C~+50° C (industrial SSD), surface air flow |
| Humidity       | 5~90° C relative humidity, non-condensing                                    |

# Widely used

Apply various life scenarios to meet your network needs.

Data centers, enterprise networks, cloud service providers, internet service providers



| Product Information |  |   |
|---------------------|--|---|
| S03                 | Intel Atom D525                          | Intel Atom Processor                      |
|                     | Intel Core 2-3th Gen I3 I5 I7            | 2th-3th Gen Intel Core I3 I5 I7 Processor |
|                     | Intel Celeron J4125                      | Intel Celeron Processor J Series          |
|                     | Intel Celeron N5105/N5100                | Intel Celeron Processor N Series          |
|                     | Intel Pentium 4405U                      | Intel Pentium Processor 4000 Series       |
|                     | Intel Core i3 1115G4/i5 1135G7/i7 1165G7 | 11 <sup>th</sup> Gen Intel Core Processor |

| Accessories List |          |  |
|------------------|----------|--|
| Item             | Quantity | Specification  |
| Power Adapter    | 1        | 12V 4A/5A  |
| Power Cord       | 1        | GB, EU,American Standard, British standard is optional |
| Warranty Card    | 1        | Neutral  |